



Peregrine Tank/Sump Heater: POHJ1386 Withdrawable Element

The PEREGRINE POHJ1386/1 and POHJ1386/2 oil/sump heaters use a withdrawable, replaceable cartridge element. This means that the element can be removed without the requirement to drain the tank or sump.

At low ambient temperatures oil has a high viscosity and this can cause drag problems with engine starting and may also cause wear on cold start-up due to poor initial oil circulation. To prevent these problems the lubricant may be warmed by an engine oil heater, which will reduce oil viscosity. PEREGRINE oil sump heaters are often fitted as a supplement to coolant pre-heaters in very low ambient temperatures and are used extensively on air-cooled engines.



Product Code	POHJ1386/1	POHJ1386/2
Wattage	500	750
Voltage	230V	
Thread/Flange	Thread	
Thread/Flange Size	1 1/4" BSP parallel with washer supplied	
Hex Size	50.8mm AF	
Immersed Length	Max 130mm	Max 200mm
Overall Length	245mm	315mm
Weatherproof	Yes	
Withdrawable	Yes	
Thermostat Temp	Non-Thermostatic	
No of Elements	One	
Element Finish	Nickel Plated & Chrome Sleeved	
Cable Length Fitted	2000mm	
Cable Armour Fitted	No	

Shipping/Warranty Information	
Shipped Dimensions (mm)	400(L) x 260(W) x 160(D)
Shipped Weight	2.5Kg
Warranty	Standard 12 months from delivery



Designed and Built in the UK

+44 (0)20 8848 1912
 sales@preheat.co.uk
www.preheat.co.uk

PREHEAT
ENGINEERING LTD