









Peregrine Coolant Heater: XW-Type (230V)

Weatherproof

PEREGRINE XW-type coolant heaters are ideally suited to large diesel engines where one, two or more heaters may be needed on a single engine and/or where there is the need for alarm operation if the heater or supply fails. All XW-type heaters are fitted with twin thermostats factory set at 50°C adjustable, one operating the heater while the second is usually set a few degrees lower to switch an independent alarm circuit should the coolant temperature fall below a pre-set temperature.



Hose: 13mm (½"), 16mm (5/8"), 19mm (¾"), 25.4mm (1"), 31.75mm (1¼") BSP: 13mm (½"), 19mm (¾"), 25.4mm (1"), 31.75mm (1¼"), 38mm (1.5")



Model	P3MXLW	P2MXLW	P1XLW	P2XLW	P3XLW	P4XLW	P5XLW	P6XLW	P7XLW	P9XLCW	P10XLCW	P12XLCW
Wattage	230	350	500	750	1000	1500	2000	2500	3000	5000	6000	8000
Weatherproof	Yes											
Voltage	230v AC											
Fluid	Water*/Coolant Mix 50%/50% or specialised coolant											
Connection Options	Hose: 13mm (½"), 16mm (5%"), 19mm (¾"), 25.4mm (1"), 31.75mm (1¼") BSP: 13mm (½"), 19mm (¾"), 25.4mm (1"), 31.75mm (1½"), 38mm (1.5")											
Heater Body Diameter	101mm											
Heater Body Length	296.50mm											
Overall Heater Length	401.25mm											
Туре	Triple Element with Control Thermostat (P12 XLC = Six Elements)											
Thermostat Range	A45, ranged 35°C - 85°C, set 50°C											
Configuration	Horizontal/Vertical with 2 x Hose Connections											
Cable	0.75²	0.75²	0.75²	0.75²	0.75²	0.75²	1.5²	1.5²	1.5²	2.5²	4² (single wires & Kopex)	4² (single wires & Kopex)
Heater Finish	Zinc Passivated Plating											
Supplied	Fixed mou	Fixed mountings 9" x 2" x 8mm, 1676mm flexible weatherproof conduit and 20mm adaptor										

^{*} The use of deionised water will prevent limescale build-up and extend the life of the heater.

Shipping/Warranty Information					
Shipped Dimensions (mm)	400 (L) x 260(W) x 160(D)				
Shipped Weight	5kg				
Warranty	Standard 12 months from delivery				













