



Peregrine Top-Entry Diesel Tank Heaters. Model: P974 Standard (230V)

PEREGRINE diesel fuel tank heaters are the ideal solution for engines operating in low ambient temperatures to reduce the risk of 'waxing' or 'gelling'. The P974 top-entry tank heater is withdrawable, thermostatically controlled and available in a variety of thread and flange sizes. All models in this range are made to order to the specific tank depth required and the elements sleeved for safety.

The wattage, size and length of the heater is dependent on the minimum ambient temperature, dimensions of the tank, amount of lagging and whether the installation is static or mobile. All models are supplied with a thermostat set at 10°C unless otherwise requested.

Model	P974/	1TT22CG	2TT22CG	3TT28CG	4TT28CG	5TT28CG	7TT28CG	10TT56CCG
Wattage		500	750	1000	1500	2250	3000	6000
Voltage	230V AC							
Weatherproof	No							
Flange Size	223mm (9") diameter							
Flange Mounting Holes	8 x 13mm							
Flange Hose Positioning	Equi-spaced on 3.875" radius							
Max Immersed Depth	As required*							
Max Horizontal Length	740mm**						1440mm**	
Connector Box Mounting	2 x 5mm studs with domed nuts							
Thermostatic Temp	10°C (adjustable -5°C to +40°C)							
No of Elements	2			3				
Element Finish	Chrome							
Cable Length Fitted	2000mm							
Cable Armour Fitted							1760mm Flexible Kopex	

* Required depth is the distance from the underside of the heater flange to the internal base of the tank

** From flange centre line to end of element



Shipping/Warranty Information

Shipped Dimensions (mm)	Will depend on size ordered
Shipped Weight	Will depend on size ordered
Warranty	Standard 12 months from delivery



Designed and Built in the UK

+44 (0)20 8848 1912
sales@preheat.co.uk
www.preheat.co.uk

PREHEAT
ENGINEERING LTD