



Specification Sheet

Peregrine Top-Entry Diesel Tank Heaters. Model: P974 Standard (415V)



All Peregrine diesel fuel tank heaters are withdrawable, thermostatically controlled and available in a variety of thread and flange sizes. All are made to order to the specific tank depth required and the elements sleeved for safety.

The wattage, size and length of the heater is dependent on the minimum ambient temperature, dimensions of the tank, amount of lagging and whether the installation is static or mobile. All models are supplied with a thermostat set at 10°C unless otherwise requested.

Model	P974/	2TT22CGZ	4TT28CGZ	5TT28CGZ	7TT28CGZ	10TT56CCGZ
Wattage		750	1500	2250	3000	6000
Voltage	415v 3-Phase					
Weatherproof	No					
Flange Size	223mm (9") diameter					
Flange Mounting Holes	8 x 13mm					
Flange Hose Positioning	Equi-spaced on 3.875" radius					
Max Immersed Depth	As required*					
Max Horizontal Length					740mm**	1440mm**
Connector Box Mounting	2 x 5mm studs with domed nuts					
Surface W/D	2.35w/cm ²					
Thermostatic Temp	10°C (adjustable -5°C to +40°C)					
No of Elements	3					
Element Finish	Chrome					
Cable Length Fitted	2000mm					
Cable Armour Fitted	1760mm Flexible					



* Required depth is the distance from the underside of the heater flange to the internal base of the tank
 ** From flange centre line to end of element

Shipping/Warranty Information	
Shipped Dimensions (mm)	Quoted at time of order
Shipped Weight	Quoted at time of order
Warranty	Standard 12 months from delivery

PEREGRINE Diesel Fuel Tank Heater Top-Entry Standard



Designed and Built in the UK

+44 (0)20 8848 1912
 sales@preheat.co.uk
 www.preheat.co.uk

