

Peregrine Top-Entry Diesel Tank Heaters. Model: P995 Weatherproof (3000W)



All **PEREGRINE diesel fuel tank heaters** are withdrawable, thermostatically controlled and available in a variety of thread and flange sizes. All are made to order to the specific tank depth required and the elements sleeved for safety.

The wattage, size and length of the heater is dependent on the minimum ambient temperature, dimensions of the tank, amount of lagging and whether the installation is static or mobile. All models are supplied with a thermostat set at 10° C unless otherwise requested.

Model P995/	7ST12CG	7ST12CGZ
Wattage	3000	3000
Voltage	230v AC/DC	415v 3ph
Weatherproof	Yes	
Flange Size	223mm (9") diameter	
Flange Mounting Holes	8 x 13mm	
Flange Hole Positioning	Equi-spaced on 3.875" radius	
Max Immersed Depth	As required*	
Element Lengths	17"	
Connector Box Mounting	4" diameter, 4 bolt with gasket	
Thermostatic Temp	Control Thermostat: 10°C (adjustable –5°C to +40°C). Over-Temp Protection Thermostat: -5°C to +40°C (adjustable –5°C to +57°C)	
No of Elements	6 x 500w/element	
Element Finish	Chrome	
Heat/Watts Density	9.23/sq inch	
Cable Length Fitted	2000mm	
Cable Armour Fitted	1760mm Flexible Kopex	
Supplied With	Gasket and a 9ӯ x 15mm thick steel weld on mating flange	



Straight Top Entry Diesel Fuel Heater

Required depth is the distance from the underside of the heater flange to the internal base of the tank

** From flange centre line to end of element

Shipping/Warranty Information		
Shipped Dimensions (mm)	Dependent on Depth	
Shipped Weight	Dependent on Depth	
Warranty	Standard 12 months from delivery	







