



Peregrine Top-Entry Diesel Tank Heaters. Model: P995 Weatherproof (4500W)



All PEREGRINE diesel fuel tank heaters are withdrawable, thermostatically controlled and available in a variety of thread and flange sizes. All are made to order to the specific tank depth required and the elements sleeved for safety.

The wattage, size and length of the heater is dependent on the minimum ambient temperature, dimensions of the tank, amount of lagging and whether the installation is static or mobile. All models are supplied with a thermostat set at 10°C unless otherwise requested.

Model	P995/	9ST19CG	9ST19CGZ
Wattage		4500	4500
Voltage		230v AC/DC	415v 3ph
Weatherproof		Yes	
Flange Size		223mm (9") diameter	
Flange Mounting Holes		8 x 13mm	
Flange Hole Positioning		Equi-spaced on 3.875" radius	
Max Immersed Depth		As required*	
Element Lengths		19"	
Connector Box Mounting		4" diameter, 4 bolt with gasket	
Thermostatic Temp		Control Thermostat: 10°C (adjustable -5°C to +40°C). Over-Temp Protection Thermostat: -5°C to +40°C (adjustable -5°C to +57°C)	
No of Elements		6 x 750w/element	
No of Disks		16	
Element Finish		Chrome	
Heat/Watts Density		9.33/sq inch	
Cable Length Fitted		2000mm	
Cable Armour Fitted		1760mm Flexible Kopex	
Supplied With		Gasket and a 9"Ø x 15mm thick steel weld on mating flange	

* Required depth is the distance from the underside of the heater flange to the internal base of the tank
** From flange centre line to end of element



**PEREGRINE P995
Straight Top Entry Diesel
Fuel Heater**

Shipping/Warranty Information	
Shipped Dimensions (mm)	Dependent on Depth
Shipped Weight	Dependent on Depth
Warranty	Standard 12 months from delivery



Designed and Built in the UK

+44 (0)20 8848 1912
sales@preheat.co.uk
www.preheat.co.uk

