



# Specification Sheet



## Peregrine Top-Entry Diesel Tank Heaters. Model: P975 Weatherproof (415V)

All Peregrine diesel fuel tank heaters are withdrawable, thermostatically controlled and available in a variety of thread and flange sizes. All are made to order to the specific tank depth required and the elements sleeved for safety.

The wattage, size and length of the heater is dependent on the minimum ambient temperature, dimensions of the tank, amount of lagging and whether the installation is static or mobile. All models are supplied with a thermostat set at 10°C unless otherwise requested.

**P975/10TT56CCGZ**  
**ATEX Zone II Compliant**



Model	P975/	1TT22CGZ	2TT22CGZ	3TT28CGZ	4TT28CGZ	5TT28CGZ	7TT28CGZ	10TT56CCGZ
Wattage		500	750	1000	1500	2250	3000	6000
Voltage	415v AC (3-Phase)							
Weatherproof	Yes							
Flange Size	223mm (9") diameter							
Flange Mounting Holes	8 x 13mm							
Flange Hose Positioning	Equi-spaced on 3.875" radius							
Max Immersed Depth	As required*							
Max Horizontal Length							1440mm**	
Connector Box Mounting	4" diameter, 4 bolt with gasket							
Thermostatic Temp	10°C (adjustable -5°C to +40°C)							
No of Elements	3							
Element Finish	Chrome							
Cable Length Fitted	2000mm							
Cable Armour Fitted	1760mm Flexible							
ATEX Zone II Compliant	Not currently						Yes	

\* Required depth is the distance from the underside of the heater flange to the internal base of the tank

\*\* From flange centre line to end of element



**Peregrine Top-Entry Diesel Tank Heater -  
Weatherproof**

Shipping/Warranty Information	
Shipped Dimensions (mm)	TBA
Shipped Weight	TBA
Warranty	Standard 12 months from delivery



Designed and Built in the UK

+44 (0)20 8848 1912  
sales@preheat.co.uk  
www.preheat.co.uk

**PREHEAT**  
ENGINEERING LTD